



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

  »

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration

- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division
Board of Directors



New Screw Shank Lubricant

Modified on Sunday, 01 February 2015 11:47 PM by [mpieler](#) Categorized as [Extrusion Hints](#)

[\(10\)](#) » [Fouling](#) » [Twin Screw](#) » [New Screw Shank Lubricant](#)



New screw shank lubricant Vol. 23 #3, Dec. 1996

When replacing or installing a new extruder screw, it is important to coat the screw shank with a thin lubricant to prevent it from rusting in place.


Molybdenum disulfide or copper based anti seize compound works well. They can be diluted in a solvent and wiped onto the shank with a rag to get a thin coating. This is a case where more is not necessarily better.

John Wagner

See also:

- [Anti seize compounds](#)
- [Check new screws](#)
- [Lubricate screw shank](#)
- [Screw installation 2](#)
- [Start new screws](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .