



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

  »

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration


- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division
Board of Directors



Gels 3

Modified on Monday, 02 February 2015 12:00 AM by [mpieler](#) Categorized as [Extrusion Hints](#) 

[\(10\)](#) » [After Rebuild](#) » [Dissimilar Metals](#) » **Gels 3**

Gels 3
Vol. 24 #1, March 1997


If the extruder die is producing gels due to polymer degradation, or die lip buildup, the use of 200 600 ppm of flouropolymer processing aid in combination with antioxidant additives can reduce these types of problems.

- Tom Butler, The Dow Chemical Co.

See also:

- [Die lip buildup](#)
- [Gel identification](#)
- [Gels 1](#)
- [Gels 2](#)
- [Improved dies](#)
- [Polymer degradation](#)
- [Purging gels](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .