



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki



Viewing /Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration

- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division
Board of Directors



powered by
screwturn wiki

Safety 2

Modified on Monday, 02 February 2015 12:34 PM by [mpieler](#) Categorized as [Extrusion Hints](#) 

[\(10\)](#) » [Thermocouples](#) » [Vector Drives](#) » **[Safety 2](#)**

Safety 2
Vol. 25 #2, Sept. 1998

Because of the constant upgrading of existing extrusion equipment, ALWAYS double check the device for electrical power before working on the equipment.

- Mark Sewak, LCI Corp.

See also:

- [Flex tube safety](#)
- [For safety's sake 1](#)
- [For safety's sake 2](#)
- [Hose clamp safety](#)
- [Razor knives](#)
- [Sweep up](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .