

JANUARY/FEBRUARY 2020



## **Composites Connection**<sup>™</sup>

**Official Newsletter of the SPE Composites Division** Reaching Over 1,000 Composites Professionals In All Industries

Sponsored by:





















**MITSUBISHI CHEMICAL** 

TARKEMA

### **Sponsor Links:**











### DSCCONSUMABLES











🙏 MITSUBISHI CHEMICAL





**Board of Directors** 

lan Swentek, Ph.D. SPE Composites Director, Chair & Auditing Committee Chair Applications Development Engineer Hexion London, ON, Canada Ian.Swentek@hexion.com



**Tim Johnson** SPE Composites Director & Treasurer Owner, President at TJohnson LLC Dayton, OH TJohnsonLLC@gmail.com



Ray G. Boeman, Ph.D. SPE Composites Director, & Memebership Chair Director, Vehicle Technology Area Michigan State University Detroit, MI



Antoine Rios, Ph.D. SPE Composites Director & Finance Chair The Madison Group Madison, WI Antoine@madisongroup. com



John P. Busel, F. ACI SPE Composites Director, Intersociety Chair & Chair-Elect V.P. Composites Growth Initiative American Composites Manufacturers Association Arlington, VA busel@armanet.org



Dale Brosius SPE Composites Director & Councilor Chief Commercialization Officer, IACMI Knoxville, TN dbrosius@iacmi.org



Uday Vaidya, Ph.D. SPE Composites Director & Education Chair Professor in Mechanical, Aerospace & Biomedical Engineering Chief Technology Officer (CTO), IACMI University of Tennessee Knoxville, TN uvaidva@utk.edu



Hicham Ghossein, Ph.D. SPE Composites Director & Award Chair President & Founder of Endeavor Hicham.ghossein@ gmail.com



Pritam Das SPE Composites Director & Newsletter Chair Senior Technical Manager Toray Composites Materials America (CMA) Tacoma, WA pdas@toraytca.com



Dale Grove, Ph.D. SPE Composites Director & Award Chair US Silica Senior Technology Product Development Berkeley Springs, WV grove.dale@hotmail.com



Andrew Rich SPE Composites Director & Communications Chair Consultant elvamk5@comcast.net



Shankar Srinivasan, Ph.D. SPE Composites Director & ANTEC Program Chair Iowa State University Economic Development Core Facility Ames, IA srigshan@iastate.edu



# Engineering plastics and polyurethanes by BASF for the automotive industry

### We turn your ideas into ideal solutions: BASF plastics for the automotive industry.

Shorter development times, enhanced performance, greater freedom in design. You do not want to settle for anything less than the perfect car. Neither do we. That is why we will stay by your side at every stage of your project with our comprehensive expertise in plastics and application development, individual parts testing, consultancy in design, simulation and much more - available to you around the world. When your idea turns into the ideal car, it's because at BASF, we create chemistry.

www.performance-materials.basf.com

### Board of Directors continued...





**Daniel T. Buckley** SPE Composites Director (Retired) Emeritus Director



**Rich Caruso** SPE Composites Director CEO Inter/Comp LLC Falmouth, MA rpcaruso@gmail.com



Michael Connolly, Ph.D. SPE Composites Director Program Manager-Urethane Composties Huntsman Polyurethanes Auburn Hills, MI michael\_connolly@hunts man.com



Frederick S. Deans SPE Composites Director Principal Allied Composite Technologies, LLC Rochester Hills, MI fdeans@alliedcomptech. com



Jack Gillespie, Ph.D. SPE Composites Director Director, Center for Composite Materials Donald C. Phillips Professor of Civil and Environmental Engineering University of Delaware Newark, DE gillespi@udel.edu



Jim Griffing SPE Composites Director & SPE Past President Boeing (Retired) Seattle, WA jsgriff1@gmail.com



Enamul Haque, Ph.D. SPE Composites Director A2H Consulting Group Enamul.Haque@ a2hconsultinggroup.com



Oleksandr G. Kravchenko, Ph.D. SPE Composites Director & Assistant Professor, Dept. of Mechanical and Aerospace Engineering Old Dominion University Norfolk, VA okravche@odu.edu

### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minute
- Education Funding
- Membership Spotlight
- Award Winning Paper



# **Sponsor the Newsletter**

### The best advertising value in the Composites Industry

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Maximize your exposure to the customers & the trade



Contact Teri Chouinard CBC, APR for more info Teri@IntuitGroup.com See page 29 for more details

### **Board of Directors** continued...





Christoph Kuhn SPE Composites Director Volkswagen Group Research Materials & Manufacturing Methods Wolfsburg, Germany christoph.kuhn@ volkswagen.de



Marcos Pantoja, Ph.D. SPE Composites Director & Next Generation Advisory Board (NGAB) Liaison Materials and Process Engineer The Boeing Company St. Louis, MO marcos.pantoja @boeing.com



Khaled W. Shahwan, Ph.D. SPE Composites Director Sr. Technology Leader -Composites, Methods & Strategies, Fiat Chrysler Automobiles (Innovation & Adv. Engineering) Auburn Hills, MI khaled.shahwan @fcagroup.com



Mingfu Zhang, Ph.D. SPE Composites Director Johns Manville Research Manager, Corporate R&D Littleton, CO mingfu.zhang@jm.com



With our diverse portfolio of innovative, high performance engineered polymers and polypropylene resins, we can provide you the tools you need to create products for a better tomorrow.





## Materials. Process. Design. Building Lighter and Safer Cars for Tomorrow.

### Forged Molding Compound

*The NEW Look of Carbon Fiber* Carbon Fiber Thermoset Composites

### SymaLITE<sup>®</sup>

Low Weight Reinforced Thermoplastics (LWRT) Composite Materials

### KyronMAX<sup>™</sup>

Advanced Chopped Carbon Fiber Engineering Thermoplastic Compounds: PA, PPA, PPS, PEI, PEAK, PAEK GMT

Glass Mat Reinforced Thermoplastics

**GMTex**<sup>®</sup> Structural Thermoplastic Composite Materials

**FUNCSTER<sup>™</sup>** Long Glass Fiber Polypropylene Composites



MITSUBISHI CHEMICAL CARBON FIBER AND COMPOSITES





Mitsubishi Chemical and our group companies are dedicated to the automotive industry, with R&D and growth in high performance composites aimed at interior, exterior and functional applications. Our focus is on developing and bringing to market lightweight, sustainable, high value and premium asthetic solutions. Look to Mitsubishi Chemical for the ultimate in range, innovation and value.



mitsubishi-chemical.com

### **Welcome New Board Memebers**



### SPE Board of Directors would like to welcome our new Directors Marcos Pantoja and Khaled Shahwan



#### Marcos Pantoja, Ph.D.

Marcos Pantoja is a Materials and Processes Engineer at Boeing currently supporting various urban air mobility platforms. Marcos received his B.S. in Chemical Engineering from UCLA and a Ph.D. in Polymer Engineering from The University of Akron. As a graduate student, Marcos was an active board member of the Akron SPE Section. Marcos helped his student chapter win several SPE Outstanding Student Chapter Awards and received the 2018 Akron Section Student Chapter Leadership Award due to his extensive involvement with the Akron SPE Section.

As a board member of the SPE Next Generation Advisory Board (NGAB), Marcos will be a liaison between the NGAB and the Composites Division. Marcos hopes to enhance overlap between both divisions and promote composites awareness within the next generation of plastics professionals.



#### Khaled W. Shahwan, Ph.D.

Dr. Khaled Shahwan is a Sr. Technology Leader – Composites, Methods & Strategies, Global Innovation & Advanced Development Engineering, FCA (Fiat Chrysler Automobiles) since 1999. Earlier, Khaled worked at Ford's Research Labs, and Advanced Vehicle Technology.

Dr. Shahwan is Chairman of USDRIVE's MTT (2014, 2017 & 2020), a member of USAMP's Steering Committee, and served as Chairman of the BoD of USCAR's Automotive Composites Consortium and a member its BoD (2008-2011). Khaled serves on: Technical Advisory Council-CAR; Industry Advisory Boards at three universities; Editorial Boards of three international journals; Technical Advisory Board-IACMI (17/18). He is an elected AIAA Associate Fellow, and an Adjunct Professor in Mechanical Engineering at Lawrence Technological University. Dr. Shahwan holds a PhD & MS-Aerospace Engineering and MS-Civil Engineering (University of Michigan), and BS-Civil Engineering (SFSU). Khaled has over 45 journal & conference publications.

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



### **Councilor Report**

#### By: Dale Brosius

he SPE Council meetings were held prior to ANTEC 2019 in Detroit, Michigan. At the beginning of proceedings, President Brian Grady called for a moment of silence to honor the passing of several distinguished SPE members, including Dr. Vicki Flaris, Thoi Ho, Dennis Hvam, and Richard G. Johnson.

All presentations and data discussed during Council meetings are available on The Chain in the Council Committee of the Whole (CCOW). We encourage everyone to take the time to review this information to get a full understanding of the Society.

### **Financial Review**

For 2018, SPE had a net positive operational result, but showed an overall deficit due to lower than expected investment results. SPE management meets on a quarterly basis with investment advisors. January 2019 results were better than budget. SPE is projecting a loss for 2019. Complete details on the 2019 budget are available on The Chain. A summary of the 2018 budget vs. actual report is available below:

	2018 Budget	2018 Actual
REVENUES		
Membership/HQ	\$ 2,062,001	\$ 2,076,477
Foundation	\$ 463,500	\$ 366, 397
HQ Events	\$ 888,500	\$ 805,372
Supported Events	\$ 348,500	\$ 396,510
Total Revenues	\$ 3,762,501	\$ 3,644,756
EXPENSES		
Membership/HQ	\$ 2,916,161	\$ 2,612,042
Foundation	\$ 589,495	\$ 456,673
HQ Events	\$ 715,781	\$ 559,365
Supported Events	\$ 22,600	\$ 10,135
Total Expenses	\$ 4,244,037	\$ 3,638,215
RESULTS		
Operational Result	\$ (481,536)	\$ 6,541
Investment / Interst	\$ 401,000	\$ (290,420)
Total Result	\$ (80,536)	\$ (283,879)



### **SPE Official Business**

Councilor Bruce Mulholland presented several proposed changes to bylaws and policies related to the budget review process and Fellows/HSM ratification procedures. Council approved both motions. All changes can be found in the official minutes.

At the end of Council I, President Grady thanked the Executive Board for their service. He also thanked Past President Al-Zubi who is now leaving the Executive Board. President-Elect Landes president the ceremonial pin to Grady and delivered the traditional "Whereas" tribute to Grady.

#### **Incoming President's Remarks**

Dr. Brian Landes of Dow Chemical begins his tenure as President of SPE (2019 - 2020). Dr. Landes delivered an inspiring talk that encouraged all SPE members to reflect upon why they joined the society and what they can do to ensure the society remains relevant and important in a changing world. His presentation included a summary of the SPE Strategic Plan that focuses on twin pillars of knowledge and networking. If SPE is to be vibrant for future generations of plastics professionals, it must make difficult decisions about resource allocation and member engagement. In keeping with the plastics zeitgeist, Landes ended his talk with a short video from The Alliance to End Plastic Waste, a global group that recently dedicated \$1.5bn to fight plastics pollution. SPE is uniquely positioned to contribute to this discussion because our strategic plan aligns with what is needed among the broader public audiences where scientific knowledge of polymer materials is lacking. This is the first step in a long journey, Landes concluded.

continued on page 9...

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



### Councilor Report continued...



#### **SPE Foundation**

Foundation Director, Eve Vitale, presented a summary of her team's work over the past year. 21,371 students experienced the PlastiVan in 2018. \$88,250 was awarded in scholarships in 2018, with 33 recipients at 21 universities. A scholarship marketing campaign was established in 2018 to increase awareness of the available scholarships in an effort to increase the number of applicants. \$64,645 in grants were awarded in 2018, some at events that were not SPEcentric, thereby increasing awareness. "Giving Tuesday" (Tuesday after Black Friday) was a success, raising \$8,985 so that 1200 new students can experience the PlastiVan.

#### Strategic Commentary ANTEC

The 2018 event, at the time of writing, was projected to achieve ~\$300k in profit for SPE. ANTEC 2020 will be in San Antonio, TX with Council starting on the 28th of March and the actual program lasting from March 30-April 2. CSE Farrey announced that AN-TEC 2021 will be held in Denver, CO from March 22-25. The public announcement included discussion of the rationale for not co-locating with NPE. Both organizations, SPE and PLASTICS, have achieved a level of success with their respective events that colocation is no longer the optimal arrangement for either group.

#### **SPE Services to Chapters**

Sandra McClelland of the SPE Finance Committee presented findings from an in-depth review of SPE staff resource allocation and chapter support requirements. As summarized by CSE Farrey, HQ provides a vast array and quantity of services that consumes a significant portion of HQ staff time and resources. The current fee model (under which some Chapters pay for services and others don't) is inequitable and unsustainable. Everyone would be better served with a clearer understanding of the services provided and the cost structure. It was decided that a small task group would be assembled to review the issue and bring a recommended revised model forward for consideration. Complete details are available on Leadership Lane.

#### SPE Sales & Marketing

SPE Business Development Manager, Stephanie Clark, reported on the advertising revenue generated in 2018. In 2019, 79 exhibitors on the floor and 37 are brand new to ANTEC. The total revenue generated from this is \$249,000. There are also 6 sponsors generating \$75,000. In total, \$360,000 was raised against an aggressive budget of \$331,990. 26 chapters and organizations have supported student activities in 2018. In 2017, there were \$270,087 of advertising sales but since that time, the total has increased to \$556,600 in just 1.5 years.

#### Additional Reports

4 new student chapters have been chartered and approved by Council:

- National Textile University
- University of Oklahoma
- Ontario Institute of Technology
- UC Berkeley

The next Council meeting is tentatively scheduled for November 14-15. Further details will be made available on The Chain.

Respectfully submitted, Conor P. Carlin VP Marketing & Communications

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



### Board Meeting Minutes Sept 3, 2019



By: John P. Busel

### SPE Composites Division Board of Directors Meeting

5:00 PM – 7:00 PM Eastern US Diamond Center, Novi, MI

### 1. Welcome

- Ian Swentek called the meeting to order at 5:00 pm.
- The group made self-introductions.
- Ian Swentek shared his vision and goals for the Composites Division. Communicating value to members is very important to the Division to further the professional nature of the industry work.

### 2. Administrative

- Ian Swentek reviewed the last meeting minutes of March 18, 2019. Dale Brosius moved to accept the minutes as written. Enamul Haque seconded. Motion passed.
- Ian Swentek reviewed the actions from the last meeting:

a. Ray Boeman to reach out to those volunteers from the Composites Division Ballot for interest and service on the Board – Not Done. Ray Boeman to follow-up.

continued on page 11..



A member of **C ALTANA** 



Ask.BYK.USA@altana.com



b. SPE Board members to provide additional names for the distribution list to solicit presentations for future ANTEC sessions. In-progress

i. Need to send Shankar/Carusothe list used to solicit ideas for topics.ii. Need to check with Dale Grovefor the list.

iii. Uday Vaidya has a list that he uses for education.

iv. Ray Boeman to provide a current list of the Division members.

c. Finance committee to develop a plan for investment strategy – Not Done.d. Finance committee to provide budget for review. Done.

e. The Awards Committee to evaluate options for new scholarship award and prepare proposal for Board. – Not done, assigned to Hicham Ghossein. f. Membership Committee to provide Division update at next Board meeting – Done g. Board members to provide update to Andy Rich for website updates – Done h. Committee chairs to provide reports for newsletter – Done.

i. Fred Deans to provide scope of new revenue activity – Not Done.

### **3. Treasurers Report**

• Tim Johnson reviewed the report that was distributed to the Board members. He reported that the Division spent more money than was taken in. This action was decided at previous meetings to spend more money for Division activities. He reviewed the proposed budget line items. The start-

continued on page 12...

### TRAIN FOR TOMORROW ENGINEERING • MANUFACTURING • REPAIR • NDI

### **ENROLL TODAY!**

Abaris Training is internationally recognized as the leader in advanced composite training with state of the art courses focusing on engineering, manufacturing, repair, & NDI.

www.abaris.com • +1.775.827.6568

# ABARIS

Leading the World in Advanced Composite Training Since 1983!



### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



ing balance is \$167,683. For the proposed FY 19/20 budget, total revenues expected is almost \$50K. Ongoing expenses include scholarships, education grants. He suggested the awards committee review the proposed amounts and report to the finance committee of any changes. There was also support for the PlastiVan and student travel awards. At the last meeting, NGAB was identified as being a new expense. Other expenses include for website, newsletter, meeting expenses, ANTEC expenses, ACCE expenses, and Councilor travel. Total expenses are almost \$61K with about \$43K for awards. It was noted that there was a late fee paid to the IRS of \$2500 for submitting the yearly tax forms late. The group discussed costs for D&O insurance for the Division. The cost does not show up because since the Division did not receive the rebate from HQ, this amount was used to pay for this insurance. Tim Johnson has inquired with HQ regarding the annual rebate that would be provided by HQ so that it could be acknowledged that this contribution by the Division.

- Andy Rich moved to accept the budget as proposed, seconded Michael Connolly. The group discussed the objective of having a balanced budget versus many years ago when budgets were underspent. It was noted that some of the line item budgets can be changed to not spend as much as proposed. Motion passed unanimously.
- Going forward, the items to be determined for the budget are the number of educational grants.

### 4. Committee Updates

• Membership: Ray Boeman reported that the Division has 637 members. In May 2019 there was 667, and in January 2019 there was 691. The change is cyclic. The breakdown is as follows: 76% is US, 6% Canada, 6% India, Asian countries outnumbered those from Germany. Ian Swentek pointed out that the membership has changed with SPE with a set fee and costs for divisions are added for each one selected. It was pointed out that the fee that is charged can be set by the division, currently at \$10.

- Awards: Ian Swentek reported the recent activity. He reference the report distributed to the Board. He reported on the recipients of the Jackie Rehkoph Scholarship. Both Automotive and Composites Division fund this scholarship. There is quite a sum of monies, but the fund is not fully funded.
- Education: Uday Vaidya referenced the report that was distributed to the Board. Several proposals were submitted for educational funding. He reviewed the basic elements of each of the proposals. It was noted that the approved budget allows for funding 2 proposals. The group discussed merits of the proposals as submitted. The proposals were scored by the committee and the top 3 were considered for funding even though the funding would exceed the approved budget. Michael Connolly moved to support the proposals from Clemson University and Western Washington University. Antoine Rios seconded. Enamul Hague amended to motion to add a 3rd proposal for consideration from Old Dominion. Mingfu Zhang seconded the amended motion. The group discussed the merits of the 3rd proposal as compared to the other two. The amended motion passed. The group voted on the top 3 proposals. The motion passed to fund the 3 proposals. Uday Vaidya asked for help from the Board to complete the judging of the posters sessions at ACCE. He thank the Board members for their help.

continued on page 13...



- Newsletter: Pritam Das reported that the revenue for the newsletter has been declining. He is working with the designer to better market the newsletter. SPE HQ should have distributed the newsletter and all board members. He noted the old logo is on Linked-in and will need to be updated.
- Communications: Christoph Kuhn reported that Twitter has been a very good platform to update the followers on Division activities. This number of followers needs to grow. The general problem for social media is to get content, especially be-

tween events like ANTEC and ACCE. Andy Rich reported the website is still in transition with SPE taking more control. Andy Rich has been working with SPE staff or appointed personnel to make updates to the website. It was noted that the award recipients would be good content for Twitter.

• Councilor: Dale Brosius asked for a proxy to attend the Council meeting and looking for volunteers. Enamul Haque volunteered to be the proxy for the Division.

EY ARKEMA

continued on page 14...

### ARKEMA'S ELIUM<sup>®</sup> LIQUID THERMOPLASTIC RESINS

PROCESSED USING TRADITIONAL THERMOSET PROCESSING METHODS

The Elium<sup>®</sup> line of resins offer:

- LIQUID AT ROOM TEMPERATURE
- EXCELLENT STRENGTH, STIFFNESS, AND TOUGHNESS
- THERMOFORMABLE PARTS
- ASSEMBLY BY WELDING
  AND ADHESIVES
- RECYCLABLE

2017 © Arkema Inc All rights reserved.





Action item details available upon request

### 5. New Business

- Ian Swentek asked for volunteers for chairelect. Two names were submitted, Fred Deans and John Busel. Fred Deans removed himself from consideration. The Board elected John Busel to be the Chair-Elect of the Composites Division. The term would be 2 years and taking over as chair at that time.
- Ian Swentek brought up the budget for the NGAB has not been finalized and needs to be addressed.

#### 6. Wrap Up

a) Ian Swentek reviewed the meeting action items.



closing the loop - today and tomorrow

### Introducing the re-Evo® brand of products



Our family of chopped carbon fiber products are ideal for thermoplastic compounding and injection molding.

Our family of non-woven products are ideal for closed/open mold infusion, pre-preg, and compression molding.



### Contact us today & join the recycling Evolution for Carbon Fiber

(843) 374-5600

www.carbonconversions.com

b) Ian Swentek reported there needs to be a chair and co-chair for ACCE. It was noted that this does not need to be a board member. Alex Kravchenko volunteered to be a co-chair representing the Composites Division as will serve as co-chair for ACCE 2020.

c) Ian Swentek reported the next meeting will be a conference call to be scheduled on December 3rd. It was also proposed for March 17, 2020, and June 16, 2020.

d) Ian Swentek acknowledged John Busel for being inducted into the ACMA's Composites Industry Hall of Fame. The Board voiced their approval and congratulations.

#### 7. Adjourn

• There was no further business to discuss. Ian Swentek adjourned the meeting at 6:53 pm.

Respectfully Submitted, John P. Busel, Secretary

#### Attendees

OFFICERS: Ian Swentek, Chair Tim Johnson, Treasurer John P. Busel, Secretary Dale Brosius, Councilor Ray Boeman, Past Chair DIRECTORS: Rich Caruso (phone) Michael Connolly Pritam Das (phone) Fred Deans (phone) John Gillespie (phone) Dale Grove (phone) Enamul Haque Alex Kravchenko Christoph Kuhn Andy Rich Uday Vaidya (phone) Mingfu Zhang

# Print Right The First Time

Additive Manufacturing Simulation for Plastics



Award winner holistic simulation platform for additive manufacturing of polymers and composites, delivering a unique combination of material engineering, process simulation and structural analysis solutions.





www.e-Xstream.com/additive-manufacturing

### **Education Funding Opportunity**



### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



#### By: Uday Vaidya

he SPE Composites Division's SPE Education Grant supports student training and exposure to state of the art Advanced Composite Materials, Design, Testing, Modeling and Manufacturing. One such example supported by SPE Composites Division is the purchase of a high temperature extruder (450 °C) at the laboratory in Advanced Composite Materials Laboratory (ACML), University of Alabama (UA). The following excerpt from Dr. Anwarul Haque, Associate Professor of the Department of Aerospace Engineering and Mechanics shares more information about the equipment purchased with SPE Composites Division's support.

"A high-temperature extruder (450 °C) has been purchased using SPE education grant to make composite filament to be used in printing high temperature composite materials in Advanced Composite Materials Laboratory (ACML), University of Alabama (UA). The laboratory is supervised by Dr. Anwarul Haque, Associate Professor of the Department of Aerospace Engineering and Mechanics. The equipment Composer 450, a high-temperature filament extruder is procured from 3devo, a Netherlands based company. The equipment is installed at







ACML, North Engineering Research Center which is a newly established research facility at UA. At present four seniorundergraduate students are working with the procured extruder to get hands-on training on manufacturing high-temperature composite filaments with Ultem, Ultem/Carbon Fiber, PEEK, and PEEK/Carbon Fiber system. Eventually, their goal is to get trained in manufacturing defect free reliable structural components using additive/digital manufacturing for aerospace applications. Previously, a group of four summer interns from Germany attended the training program at the ACML and processed PLA/ Carbon Fiber filaments and eventually studied the tensile and fracture properties of the processed composites. A recent Ph.D. graduate has also used the equipment extensively in his final year of dissertation as a part of his research and the outcome of the related work is pending journal publication. Apart from the regular research group of ACML, different student bodies from the undergraduatelevel Aircraft Design and Testing (AEM 451) and graduatelevel Composite Materials (AEM 552) courses visit the lab and get hands on experience on additive manufacturing (AM) using the Composer 450. An abstract has been accepted to a National conference focusing additively manufactured high temperature polymer matrix composites."

Composites Connection

### **Membership Spotlight**



### **SPE Composites Division Membership by Country**





#### JM ADVANCED COMPOSITES WE CREATE FUNCTION-FOCUSED ORGANOSHEETS FOR LIGHTWEIGHT APPLICATIONS



- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minute
- Education Funding
- Membership Spotlight
- Award Winning Paper





### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



### **Award Winning Paper**

### **Direct Fiber Model Validation:** Orientation Evolution in Simple Shear Flow

Sara Andrea Simon, Abrahán Bechara Senior, Tim A. Osswald Polymer Engineering Center, University of Wisconsin-Madison

#### Abstract

irect particle models are a promising tool for predicting microstructural properties of fiber reinforced composites. In order to validate our modeling approach for fiber orientation prediction, compression molded reinforced Polypropylene samples were subjected to a simple shear flow in a Sliding Plate Rheometer. Micro computed tomography was used to measure the orientation tensor for deformations up to 60 shear strain units. The fully characterized microstructure at zero shear strain was used to reproduce the initial conditions in the particle simulation. Fibers were placed in a periodic boundary cell and a flow field matching the experiment was applied. Samples created with the proposed compression molding technique showed repeatable and controlled initial orientation. The model showed good agreement with the steady state orientation; however, it showed a faster orientation evolution at the start of the shearing process.

#### Introduction

Computational tools to simulate the processing of fiber reinforced composites have become indispensable for the automotive industry. The ability to accurately predict the microstructure of molded components is a key factor not only for design calculations but also for addressing issues such as shrinkage and warpage before mold fabrication. Almost all commercially implemented models (Folgar-Tucker, Anisotropy Rotary Diffusion (ARD) Reduced Strain Closure (RSC)) use experimentally determined fitting parameters. However, these experiments are costly, lengthy and limited in the amount of information they can provide. Particle level simulations have been used in the past to aid in the understanding of these type of systems [1, 2]. In these simulations, each fiber is modeled individually as a chain of rigid elements. Fibers are placed in a predetermined flow field and hydrodynamic forces, as well as fiber-fiber interactions, are computed to predict fiber motion [3, 4].

Obtaining parameters numerically has advantages over obtaining them experimentally. In a numerical setup, all parameters can be accurately controlled, detailed information is always available and the simulations are relatively inexpensive to perform. An additional advantage of these models is the high accuracy that is reached by modeling the actual motion of individual fibers [5].

The objective of this paper is to provide reliable fiber orientation evolution data in a well-defined simple shear flow to aid in the validation and development of a multi-particle model for reinforcing fibers. Simple shear was chosen since it is one of the fundamental flow conditions present in most polymer processes. Selecting it allows us to directly correlate the rate of deformation with the filler's behavior. Compression molded glass fiber-reinforced polypropylene samples were sheared in a Sliding Plate Rheometer following Cieslinski et al. [6]. As has been shown by the same author, compression molding is not a suitable sample preparation method since it has no control over the planar orientation of the fibers. In this work, we will therefore present a compression molding technique which

continued on page 20...

Composites Connection



### Fit for any environment.

Our plastics can operate in many environments, taking the requirements of any job in stride. Our innovative spirit drives the creation of next-generation lightweight material solutions capable of adapting to any specification. From flame retardancy to withstanding mechanical loads, our high-performance plastics are stronger, safer, and more effective components.

Find your next adaptable plastic at dsm.com/plastics.



ensures a controlled and repeatable initial fiber orientation for shear experiments. Results from both simulation and experiment are compared.

#### Experimental Sample preparation

The material used in this work was a commercially available glass fiber-reinforced polypropylene with 20 %wt. fiber content (SABIC<sup>®</sup>, STAMAX 20YM240). The material properties are listed in Table 1.

Material Property	Value
Nominal Fiber Density [%vol]	8.2
Nominal Fiber Length [mm]	15
Fiber Diameter [µm]	19±1
Density of Fibers [g/cm <sup>3</sup> ]	2.55
Density of Composite [g/cm <sup>3</sup> ]	1.04
Density of Polypropylene [g/cm <sup>3</sup> ]	0.91

Table 1: SABIC® STAMAX 20YM240material properties



Samples for the sliding plate rheometer (SPR) were prepared by compression molding extruded strands. Compression molding was chosen as the sample preparation method to obtain a simple, repeatable and controlled initial fiber orientation (FO). Starting with identic initial FO is important to accurately validate the proposed direct fiber model. Previous work [6, 7] has shown that samples created with injection molding also provide a repeatable initial FO, however, injection molded specimen show a more complex core shell structure [8], which is it difficult to reproduce computationally.

The material was received as 15 mm long pellets created through a pultrusion process where the length of the fibers is identical to the pellet length. This means that fibers are not dispersed within the matrix. In order to disperse the fibers, the material was first processed in an Extrudex Kunststoffmaschinen single screw extruder with a smooth barrel (EDN 45X30D). The 45 mm 30 L/D extruder was equipped with a gradually tapering screw and a 3 mm die. The processing settings were based on the processing guidelines provided by SABIC<sup>®</sup>. The seven temperature zones of the extruder were set to 210, 210, 220, 220, 230, 230 and 230 °C, respectively. The composite was extruded at 5 rpm. The extrudates were pulled by a Conair precision puller to ensure homogenous strands.

Due to the low extrusion speed, most of the initial fiber length (FL) was maintained after processing, giving a number average fiber length  $(L_N)$  of 6.7 mm and a weight average fiber length  $(L_W)$  of 11.4 mm. The maximum detected FL showed the initial pellet length of 15 mm. The FL measurements follow the method developed at the Polymer Engineering Center and will be described in the following chapter.

continued on page 21...

Composites Connection



Computational time for the mechanistic model simulation is geometrically proportional to the maximum detected FL. In order to reduce computation, the strands were pelletized to 3.2 mm. Initial trials showed that alignment of pellets in the mold did not yield a repeatable initial FO as, during compression, pellets could move easily and rotate. Therefore, pellets were re-extruded and strands were cut to the mold dimensions. Analysis of the strands showed a LN of 0.83 mm and  $L_w$  of 1.53 mm and a maximum detected FL of 4 mm. The mold geometry used in this study was a rectangular prism (14 mm x 14 mm x 2.1 mm).

The top and the bottom of the mold were coated with aluminum foil to facilitate sample extraction. The bottom half of the mold was placed on a heating plate to cause partial melting of the aligned strands (Figure 1a, 1b). The resulting plate was flipped and re-molten; this second step was needed to remove air bubbles caught between strands.



### Custom Press Systems & Technology



DAIMLER-CHRYSLER



SUPPLIED TO FORD MOTOR COMPANY





Since 1854, Williams, White has engineered and manufactured custom hydraulic press technology for leading automotive companies and Tier 1 suppliers. Utilizing the latest in 3-D modeling and finite element analysis, we will custom design your next press for assured repeatability, continuous production and unprecedented performance.



Figure 1: Sample preparation steps. (a) alignment of strands, (b) partial melting of strands, (c) compression molding.

The plates were then compression molded with a Carver compression molding machine (Model 3889.1NE1000) (Figure 1c). The two platens were heated to 210 °C and a load of 1000 lbs was applied for 2 minutes. After compression, the plates were sandwiched between two cold steel plates to prevent warpage. The fiber properties (FO, FL and fiber density distribution) of the final plates were analyzed and the results are summarized in Table 2. Multiple samples were taken within a compression molded plate to ensure homogeneity.

Material Property	Value
a <sub>11</sub> [-]	0.86
a <sub>22</sub> [-]	0.11
a <sub>33</sub> [-]	0.03
Fiber concentration [%vol]	7.93
L <sub>N</sub> [mm]	0.83
L <sub>w</sub> [mm]	1.53

Table 2: Average fiber properties of compression molded plates, with  $a_{11}$  (extrusion direction),  $a_{22}$  and  $a_{33}$  as the orientation tensors.

continued on page 22...



#### **Sliding Plate experiment**

FO evolution as a function of shear strain was determined by shearing compression molded samples in a SPR under a controlled simple shear flow. The SPR was based on the design of Giacomin et al. [9]. This rheometer was chosen over a rotational rhaometer to overcome curvature effects observed in previous work [6]. The SPR rheometer used in this study is shown in Figure 2.



Figure 2: Sliding Plate Rheometer assembly.

The SPR has an effective surface of 100 x 300 mm<sup>2</sup>, a maximum stroke of 120 mm and a gap size of 2 mm. The maximum displacement and the fixed gap size limit the deformation that can be imposed on the sample to a maximum shear strain of 60. The SPR rests inside a forced convection oven and the sliding plate is moved by an Interlaken 3300 test frame.

The experimental procedure is based on Cieslinski et al. [6]. The rheometer was heated to 260 °C for 2 hours prior to sample loading. Upon loading, the test specimen was rotated 90° with respect to the extrusion direction, effectively swapping the a, with the a<sub>22</sub> tensor. This was done to have the experiment start with a low alignment in the shearing direction so a larger change in orientation could be observed. The samples were secured between the rheometer plates and allowed to melt evenly before tightening the screws to a final gap of 2 mm (Figure 3a). Since the initial thickness of the compression molded plates was 2.1 mm, the sample was slightly compressed when tightening the plates to guarantee full contact. After an additional 10 minutes of heating the sample was sheared at a rate of 1 s<sup>-1</sup> (Figure 3b). Forced convection was used to accelerate the cooling of the sample in the rheometer to preserve its shape and FO. Once room temperature was reached, the sample was extracted and cut for analysis (Figure 3c). Six repetitions per testing condition were used to ensure accuracy and repeatability of results.

continued on page 24...

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



# Proven performance in the most demanding applications

From high-performance structural adhesives to stronger, faster composite resin systems, Huntsman understands the demands for faster processing and reduced production cycles. With over 60 years' experience developing adhesive and composite resin technologies, Huntsman scientists work with designers and engineers every day to help solve increasingly complex design issues.

Give us your challenge and see what we can do.





Enriching lives through innovation





Figure 3: Sliding Plate Rheometer procedure, (a) Compression of molten sample during loading, (b) shearing of sample, (c) sample extraction for fiber orientation analysis; dark region represents area of pure shear.

### Measurement of fiber microstructure

A fully characterized microstructure is required to accurately reproduce the initial conditions in the mechanistic model simulation. The in-plane microstructure analysis involved determining the fiber concentration as well as the fiber length. Analysis of the thickness-wise microstructure included determining the fiber volume fraction and the fiber orientation. A detailed description of the employed analysis techniques is given in the following paragraphs.

This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



# Sponsor the Newsletter

## The best advertising value in the Composites Industry

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Maximize your exposure to the customers & the trade

Contact Teri Chouinard CBC, APR for more info Teri@IntuitGroup.com

See page 29 for more details

# COMPOSITES

#### **Fiber Orientation Characterization**

FO was measured by using the micro computed tomography (µCT) technology approach (Figure 4). For the measurement an X-ray source illuminated the specimen which was fixed on a rotating platform. The X-rays passed through the sample and were attenuated by the material. Depending on the configuration of the constituents of the sample, the energy of the X-rays was absorbed differently. A detector recorded the attenuated Xrays as radiographs at each predetermined angle. A full 3D representation of the sample was generated by all radiographs [8, 10]. The µCT data set was then further processed by using the VG StudioMAX (Volume Graphics) software. This software has an implemented tool for FO analysis and quantifies the FO using the structure tensor approach [11].



Figure 4: Schematic of the micro computed tomography system used in this study. Image was adapted from [8].

continued on page 25...



Samples were scanned with a Metrotom 800  $\mu$ CT system (Carl Zeiss AG). The used scan parameters are summarized in Table 3.

80
100
1000
8
3.5
2200

Table 3: Micro computed tomography settings

#### Fiber Length Characterization

The FL was determined by using the FL measurement concept developed at the Polymer Engineering Center, UW-Madison. This technique consists of a time-efficient dispersion system and a fully automated image-processing algorithm to measure a large amount of fibers.

As even small samples might contain several million fibers this measurement technique applies a downsampling step based on the method proposed by Kunc et al. [12]. Coupons were cut out, transferred into specially designed perforated brass sample holders and a weight was put on top. The container and the added weight act as a constraint to help to maintain the original sample size and prevent the fiber network from expanding during pyrolysis. The polymer matrix was burned off for a period of 2 hours at 500 °C. To obtain a sub-sample of the ashed fibers a hypodermic needle was centrically inserted through a needle guide into the fiber network and a column of resin was injected. The resin was cured with a LED Flashlight. A second burn-off for a period of 1.5 hours at 500 °C was performed to remove the resin [12, 13].

As a next step the fibers were dispersed through an air dispersion chamber using bursts of compressed air at 1.5 bar. Due to the turbulences in the enclosed system a disentanglement and a uniform dispersion of the fibers on glass plates can be achieved. The fibers were then scanned at 2400 dpi. The scanned image was processed and enhanced in Photoshop. A binary image was created by using a thresholding technique.

The Marching Ball image processing algorithm was employed in this work as it automatically detects single fibers and quantifies the fiber length distribution (FLD). The algorithm can identify bent as well as intersecting fibers, which is particularly important for long fiber reinforced composites. At least 30,000 fibers were analyzed for each sample.

It is known that down-sampling methods result in skewing the FLD. Thus, the Kunc correction function was used for all FL values to provide an unbiased FLD (Equation 1).

$$N(L) = \Phi(L) \left(1 + \frac{4L}{\pi d}\right)^{-1}$$

Equation 1: Corrected number of fibers of a certain length N(L), where  $\Phi(L)$  is the number of fibers of length L and d the diameter of the glue column, respectively [12].

The output of the analysis is a data set consisting of the individual lengths of all fibers. This raw data set needs to be statistically processed in order to obtain comparable results, such as the FLD,  $L_N$  and  $L_W$ . The FLD and the average values can be calculated according to equation 2-4.

continued on page 26...

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



$$W(L_i) = P(l \le L_i) = \sum_{i=0}^{L_i} \frac{N_i}{n}$$

Award Winning Paper continued...

Equation 2: Cumulative FLD W, which gives the probability that fibers of length l are shorter than a certain value  $L_i$ . W is calculated by summating the relative frequency of each length interval (quotient of the number of fibers of a certain length  $N_i$  divided by the total number of fibers n) [10].

$$L_N = \frac{\sum_i N_i l_i}{\sum_i N_i}$$

Equation 3: Number average FL,  $L_N$ . The lengths li span the range of the data.  $N_i$  is the number of fibers with lengths between  $l_i - \Delta l/2$  and  $l_i + \Delta l/2$  ( $\Delta l$  is the experimental bin width and a set of length values  $l_i$  such that  $l_i + 1 = l_i + \Delta l$ ) [10, 14, 15, 16].

$$L_W = \frac{\sum N_i \, l_i^2}{\sum N_i \, l_i}$$

Equation 4: Weight average FL,  $L_w$ . The lengths li span the range of the data.  $N_i$  is the number of fibers with lengths between  $l_i$ - $\Delta l/2$  and  $l_i$ + $\Delta l/2$  ( $\Delta l$  is the experimental bin width and a set of length values  $l_i$  such that  $l_i$ +1= $l_i$ + $\Delta l$ ) [10, 14, 15, 16].

#### **Fiber Concentration Characterization**

The local fiber density was obtained by determining the fiber weight fraction through pyrolysis at a temperature of 500 °C for 2 hours. The specimen was weighed before and after pyrolysis and the fiber volume fraction was determined according to Equation 5:

$$V_f = \frac{v_f}{v_c} \times 100$$

Equation 5: Fiber volume fraction  $V_f$  in %vol, with  $v_f$  as the volume of the fiber in g/cm<sup>3</sup> and  $v_c$  as the volume of the composite material in g/cm<sup>3</sup>, respectively.

This method is a quick and effective way to determine the average fiber volume fraction, but it does not give any information on the fiber concentration (FC) in each layer of the sample. Pyrolysis can also be used to study the FC in the thickness direction. However, this approach requires the collection of material of several sample layers through the thickness. For each data point the sample would need to be prepared by grinding. As has been reported in literature, this approach is not only cumbersome and time consuming, but also leads to errors in analysis [8].

We will therefore use the  $\mu$ CT approach to determine the fiber density through sample thickness. The layer wise FC was quantified with VG StudioMAX (Volume Graphics) software. In this approach the  $\mu$ CT data set is converted into a stack of 2D cross-sectional images aligned normal to the thickness direction. These grayscale images are transformed into binary images by thresholding, which separates the image into black (matrix) and white (fibers) pixels. Subsequently, the fiber volume fraction through the thickness is calculated [8].

continued on page 27...



#### **Modeling and Simulation**

#### **Single Particle Model**

The computational model, subject of this study, is based on the work done by Schmid et al. [17]. Each fiber is represented by a chain of rigid segments connected with spherical joints. Particle inertia is neglected in anticipation of the low Reynolds numbers characteristic of viscous suspensions. Extensional and torsional deformations are neglected as well. There is no Brownian motion and no buoyant effects. As shown in Figure 5a, a segment is hydrodynamically represented as a chain of beads. The force ( $F^i$ ) and torque ( $T^i$ ) exerted by the fluid on an individual segment are computed through the hydrodynamic force ( $F^k$ ) and torque ( $T^k$ ) acting on spheres located along the segment's axis ( $r_k$ ).



Figure 5: (a) Hydrodynamic representation of segments, (b) Fiber interaction is depicted. The contact force is different than zero when  $d_{ii} < D$  [3].

continued on page 28...

### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minute
- Education Funding
- Membership Spotlight
- Award Winning Paper



## **Sponsor the Newsletter**

### The best advertising value in the Composites Industry

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Maximize your exposure to the customers & the trade



Contact Teri Chouinard CBC, APR for more info Teri@IntuitGroup.com See page 29 for more details



The contact force between fibers is treated with a discrete penalty method. Penalty methods work by detecting proximity between colliding objects and applying a repulsive "penalty" fo rce when the distance  $(d_{ij})$ to the collision target is small, increasing the strength of repulsion force as distance decreases (Figure 5b).

After defining the rules of motion for a single fiber, a simulation can be set up by placing a representative number of fibers in a unit cell and imposing a flow field (Figure 6). Periodic conditions are defined in the boundaries perpendicular to the flow direction in order to guarantee a constant fiber volume fraction. Fibers exiting through these boundaries are cloned as reent ering fibers. "Ghost" cells are placed adjacent to the periodic boundaries to maintain continuity in the force calculation (Figure 6).



Figure 6: Unit cell with periodic boundary conditions. Image adapted from [3].

#### **Reproducing Initial Conditions**

As noted by Cieslinski et al. [6] accurate and repeatable initial conditions are needed for obtaining reliable rheological data. For this purpose, the microstructure of the experimental samples was carefully characterized and used to generate a matching cluster of fibers for the simulation. In the pre-processing stage of the simulation, global values of orientation  $(a_{ij})$ , fiber density (%vol) and average fiber length  $(L_N, L_W)$  can be assigned to a cluster of fibers. Since the experimental samples do not show homogeneous microstructure through the thickness, a discrete approach must be taken in order to reproduce these characteristics.

### Discretization of Fiber Density and Fiber Orientation

 $\mu$ CT analysis generates a continuous set of fiber volume fraction and orientation tensors across the thickness of the sample; this thickness was discretized into 10 segments ( $\Delta$ t=0.2 mm) and the continuous values were averaged per each segment as shown in Figure 7 and Figure 8.



Figure 7: Discretization of fiber concentration through thickness.

continued on page 29...

### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



Composites Connection

It is worth noticing that the maximum number of segments that can be used is limited by the  $a_{33}$  component of orientation. As the thickness of the individual clusters reduces, achieving a desired value of orientation in that direction becomes unattainable.



Figure 8: Discretization of fiber orientation through thickness.

#### **Average Fiber Length Reproduction**

The experimental FL is given in the form of number and weight averages ( $L_N 0.83 \text{ mm}$ ,  $L_W 1.53 \text{ mm}$ ). The cell's volume and the global fiber volume fraction are used to calculate the cumulative length of the fibers. This cumulative length is then broken down into individual length bins until the length distribution averages match the experimental values (Figure 9a).

continued on page 30...

# **Sponsor the Newsletter**

### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minute
- Education Funding
- Membership Spotlight
- Award Winning Paper



Quarter page ad or logo ad: 3.75" x 5"	\$500
Half page ad: 7.5" x 5.5", 5" x 7.5", 4" x 8.5"	\$750
Full page ad: 7" x 10", 8.5" x 11"	\$1,250
<b>Contact:</b> Teri Chouinard CBC, APR SPE Composites Division Sponsorship Chair C/O Intuit Group, Inc. phone 248.701.8003 Teri@IntuitGroup.com	

Please provide Logos as JPG and EPS files (send both if possible) Please provide Ads as High Resolution PDF files Advertising with the SPE Composites Division is inexpensive and easy. Please help us to promote the benefits of Composites in Industry.

Sponsoring the Newsletter enables the SPE to communicate the benefits of the composites in many industries, which fortifies your marketing efforts.

Composites Connection

- Support your SPE Composites Division
- Reach 1,000 Composites Professionals 3 Times a year via the E-Newsletter
- Also reach 1,070 SPE Composites Division Linked In Members 3 times a year and an additional 11,492 COMPOSITES Linked In Members Secondary group where the link to the newsletter is posted year-round
- Reach many more as a sponsorship also includes your logo on our website, www.composites.4speorg with a link to your company
- Maximize your exposure to the customers & the trade
- Stay informed on the latest composites activity

Increase your presence on the web leading to more sales by sponsoring our Electronic Newsletter which is published on the SPE Composites Division Website and emailed to all Division Members (1,000 approx.) 3 times annually. Rates include 3 issues (not on calendar basis - published approx. Nov/Dec, Mar/April, July/August). All ads include a link to your website increasing your exposure on the worldwide web exponentially. Sponsorship also includes your logo ad with a link to your website on <u>www.composites.4speorg</u> further increasing your presence on the Web as a Leader in Composites Technology.







When placing the fibers inside the unit cell, fibers of same length are distributed equally among the individual angle bins, thus guaranteeing equal length representation for every orientation (Figure 9b). Longer fibers start populating the cell first, then progressively shorter fibers fill in the remaining volume until the desired volume fraction is achieved. Finally, all individual clusters are stacked in the same sequence as the discretized data to create the complete microstructure as shown in Figure 10.

continued on page 31...



Figure 10: Computational cluster, with x as the shearing direction.

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper





### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



### Award Winning Paper continued...

#### Simulation

To match the experimental conditions, a simple shear flow field was imposed on the unit cell with a rate of deformation of 1 s<sup>-1</sup>. The viscosity was calculated using the experimental temperature, rate of deformation and properties of the neat polypropylene. The dimensions of the cell are dictated by the sliding plate gap in Z direction of 2 mm and the maximum FL of 4 mm. In order to allow free rotation, the dimension in X and Y were set to 11 x the maximum FL. The simulation time was set to 60 seconds to reach the total deformation of 60. Cell walls parallel to planes XZ and YZ have a periodic boundary condition. A tight array of static fibers was placed on the upper and lower boundaries to emulate the SPR walls. The simulation outputs the nodal coordinates of each fiber at every time step. With this information both global and thickness wise orientation tensors can be calculated. After the sliding plate was tightened to the final gap thickness of 2 mm the orientation tensors changed from the values reported in Table 2. The actual values corresponding to the initial conditions are listed in Table 4.

Material Property	Experimental	Computational
a <sub>11</sub> [-]	0.36	0.36
a <sub>22</sub> [-]	0.59	0.62
a <sub>33</sub> [-]	0.05	0.02

Table 4: Experimental and computational orientation tensors used to reproduce initial conditions.

#### **Results and Discussion**

Global diagonal components of the orientation tensor as a function of shear strain are shown in Figure 11. The all component starts at 0.36 and transitions to a steady state value of around 0.7 for both the experiment and the simulation. The steady state is reached at a total strain of 50, again, for both cases. Since this material falls in the category of long fiber composites, values of a33 component are expected to be low since long fibers will orient mostly on the XY plane. Experimental values at zero strain show a low standard deviation which demonstrates a repeatable initial FO, validating the sample preparation method. From the start, the simulation shows faster orientation evolution than the experiment. This phenomenon has also been reported in literature [18] for other diffusion models. Jeffrey's Hydrodynamic model is based on Jeffrey's equation for the motion of a single fiber which was later modified with an isotropic rotary diffusion term to account for fiber-fiber interactions. It has been proven that this model always predicts faster orientation kinetics in a transient state when compared to related experiments. This issue was addressed by combining the Hydrodynamic model with the ARD model. However, results still showed the initial quicker rate of orientation [18]. To treat this fast response problem of orientation, Wang et al. [19] developed a new evolution equation of the second orientation tensor and named his model the RSC model. This model still shows a slightly quicker initial rise of flow-direction orientation (all) but achieves nearly the same steady orientation states as obtained with experiments [18]. A recent study by Mezi et al. [20] addresses a current issue with direct particle approaches, namely, the missing coupling between particle and fluid i.e. the models only consider hydrodynamic forces acting on the particles but not the ef-



fect of particles on the surrounding fluid. When the effect of particle motion on the flow field is accounted for, the effective shear rate decreases in value leading to a slower orientation evolution. However, implementing this coupling is extremely costly computationally, therefore it was not implemented in this work.

The experimental core-shell structure is largely unchanged at 12.5 strain units when compared to the initial orientation (Figure 12). At the same applied strain, the simulation already shows a large transition to a rather homogenous structure. This once again shows that the direct particle model exhibits a faster orientation evolution. Once 60 strain units are reached, the coreshell profile disappears and a good match between experiment and simulation can be observed. It is assumed that shearing beyond 60 strain units would lead to fiber orientations which would be constant throughout the thickness demonstrating a steady state FO [6].

The simulation results for all through thickness were smoothed and plotted for different strains in Figure 13. Under a constant shear the heterogeneous orientation profile transitions into a homogeneous steady state. The most significant change in orientation occurs in the core of the sample. The rate of change slows down as orientation approaches steady state. This aligns with results published in literature [6] as well as previous work with injection molded plaques [7].

continued on page 33...



Figure 11: Experimental (black) and predicted (red) fiber orientation evolution.

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper





### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



### Award Winning Paper continued...



Figure 12: Experimental (black) and predicted (red) all values through sample thickness at varying shear strains.

continued on page 34...



 $\mu$ -CT data (Figure 14) also shows fiber alignment in the flow direction and underlines the trend seen in Figure 13. The green/blue regions demonstrate fibers which are aligned with the flow direction, characterized by large values of a<sub>11</sub> and low values of a<sub>22</sub>, whereas red regions represent a crossflow orientation

state, with low values of  $a_{11}$  and high values of  $a_{22}$ . Yellow indicates fibers which are oriented in the thickness direction  $(a_{33})$ . This color is almost absent in Figure 14 which indicates a nearly planar orientation state [18]. The clearly define core-shell structure becomes homogeneous after shearing.







Figure 14:  $\mu$ CT FO through thickness from VG StudioMax analysis, top: 0 shear strain, bottom: 60 shear strain.

continued on page 35...

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper





### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper



A particle-level simulation for reinforcing fibers was successfully used to determine the FO evolution. Results showed good agreement with the steady state orientation tensor. In its current state the model can be employed for two main tasks: firstly, the periodic boundary cell can be used as a numerical rheometer, where correlations between process parameters and fiber properties are established. This is especially useful for determining fitting parameters for commercially implemented continuum models [1]. Secondly, the model can be coupled with mold filling simulations in order to study fiber motion and fiber-mold interaction in small scale geometries; for example, fiber matrix separation during rib filling [2] or FO in the flow front [21].

A reliable method for preparation of samples for suspension rheology was developed. Repeatable and controlled initial orientation can be achieved through the presented compression molding technique.

Next steps of this project include:

- 1. Reproducing further experiments conducted by Cieslinski et al. [6] with different FC to evaluate the impact of coupling in the direct fiber model.
- 2. Repeating the study with an extensional flow to gain insight on this fundamental type of flow.
- Predicting the FO evolution with currently employed diffusion models which are based on the orientation tensor scale to evaluate how the mechanistic model performs.

This future work will be used to evaluate the model and aid in its development. Additionally, a better understanding of the underlying physics of the motion of fibers and their interaction in concentrated regimes can be gained.

#### Acknowledgements

This material is based upon work supported by the National Science Foundation under Grant No. 1633967. The authors would like to thank SABIC<sup>®</sup> for their continuous support and collaboration with our research group and their material supply. Additionally, we would also like to thank our colleagues from the Polymer Engineering Center who provided insight and expertise that greatly assisted the research.

### Bibliography

- [1] C. Perez, "Particel level simulation of fiber motion to determine continuum based models parameters for fiber orientation prediction," in ECCM17 - 17th European Conference on Composite Materials, Munich, 2016.
- [2] C. Kuhn, "Simulative Prediction of Fiber-Matrix Separation in Rib Filling During Compression Molding Using a Direct Fiber Simulation," Journal of Composites Science, vol. 2, no. 1, 2018.
- [3] C. Perez, "The use of a direct particle simulation to predict fiber motion in polymer processing," Dissertation - University of Wisconsin-Madison, 2016.
- [4] E. Baur, S. Goris, D. Ramirez, P. Schmidtke and T. Osswald, "Mechanistic model to determine fiber orientation simulation material parameters," Proceedings of the Annual Technical Conference of the Society of Plastics Engineers, Las Vegas, NV, 2014.
- [5] U. Strautins, "Flow-driven orientation dynamics in two classes of fibre suspensions," Dissertation - Fachbereich Mathematic der Technischen Universität Kaiserslauten, 2008.
- [6] M. J. Cieslinski and D. Baird, "Obtaining repeatable initial fiber orientation for the transient rheology of fiber suspensions in simple shear flow," Journal of Rheology, pp. 161-174, 2015.

continued on page 36...



### This Issue:

- BOD Listings
- Welcome New BOD
- Councilor Report
- Board Meeting Minutes
- Education Funding
- Membership Spotlight
- Award Winning Paper

- [7] S. Simon, A. Bechara Senior and T. Osswald, Predicting Fiber Orientation Evolution using Particle-level Simulation: An Experimental Validation, Poster at Automotive Composites Conference & Exhibition, 2018.
- [8] S. Goris, "Characterization of the process-induced fiber configuration of long glass fiber-reinforced thermoplastics," Dissertation, University of Wisconsin-Madison, 2017.
- [9] A. Giacomin and J. Dealy, "A novel sliding plate rheometer for molten plastics," Polymer Eningeering Science, vol. 29, pp. 499-504, 1989.
- [10] B. N. Nguyen, S. Bapanapalli, J. Holbery, M. Smith, V. Kunc, B. Frame, J. Phelps and C. Tucker, "Fiber length and orientation in long fiber injection molded thermoplastics," Journal of Composite Materials, vol. 42, no. 10:1003, 2008.
- [11] M. Krause, B. Hausherr, C. Burgeth and W. Krenkel, "Determination of the fibre orientation in composites using the structure tensor and local X-ray transform," Journal of Materials Science, vol. 45, no. 4, p. 888, 2009.
- [12] V. Kunc, B. Frame, B. Nguyen and G. Velez-Garcia, "Fiber length distribution measurement for long glass and carbon fiber reinforced injection molded thermoplastics," in 7th Annual Society of Plastic Engineers Automotive Composites Conference & Exhibition, MI, Troy, 2007.
- [13] J. Phelps, A. El-Rahman and V. Kunc,
  "A model for fiber length attrition in injection-molded long-fiber composites,"
   Composites Part A, pp. 11-21, 2013.
- [14] U. Yilmazer and M. Cansever, "Effects of processing conditions on the fiber length distribution and mechanical properties

of glass fibre reinforced nylon-6," Polymer Composites, vol. 23, no. No. 1, 2002.

- [15] P. Ren and G. Dai, "Fiber dispersion and breakage in deep screw channel during processing of long-fiber reinforced polypropylene," Fibers and Polymers, vol. 15, pp. 1507-1516, 2014.
- [16] J. Wang, C. Geng, F. Luo, Y. Liu, K. Wang, Q. Fu and B. He, "Shear induced fiber orientation, fiber breakage and matrix molecular orientation in long glass fiber reinforced polypropylene composites," Materials Science and Engineering A, pp. 3169-3176.
- [17] C. Schmid, L. Switzer and D. Klingenberg, "Simulations of fiber flocculation: effects of fiber properties and interfiber friction," Journal of Rheology, vol. 44, pp. 781-809, 2000.
- [18] M. Wang, R. Chang and C. Hsu, Molding Simulation: Theory and Practice, Carl Hanser Verlag, 2018.
- [19] J. Wang, R. Chang and C. Hsu, "An objective model for slow orientation kinetics in concentrated fiber suspensions: Theory and Rheological evidence," Journal of Rheology, vol. 52, pp. 1179-1200, 2016.
- [20] D. Mezi, "Fiber suspension in 2D nonhomogeneous flow: The effects of flow/fiber coupling," Journal of Rheology, vol. 63, no. 3, pp. 405-418, 2019.
- [21] A. Bechara, S. Kollert, J. Onken, D. Ramirez and T. Osswald, "Effect of fountain flow on fiber orientation and distribution in fiber filled polymers during mold filling," in ANTEC, Las Vegas, 2013.



# **TOPCON 2020**





Announcing the SPE Thermoset TOPCON 2020 event in Madison, Wisconsin at the beautiful Monona Terrace Community and Convention Center. Join the leaders in the industry and learn about opportunities for thermoset innovative technologies in multiple markets.

## Automotive – Agricultural – Aeorspace Heavy Truck – Wind Energy – Marine – Medical – Electro/Electronics – Outdoor Sporting Goods & More!

Enjoy networking during breakfast, lunch and a first class cocktail reception all included with your registration.



TOP INDUSTRY

INNOVATIONS

Sponsor and/or exhibit at the event and feature the latest thermoset products and services. Networking breakfasts, lunches and the cocktail receptions will be in the exhibit area enhancing sales opportunities and corporate exposure.

With pristine views of Lake Monona from the Community Terrace exhibit area, you and your customers will have a relaxing and enjoyable experience!

Present your innovative thermoset products, services and technologies from the stage of the very comfortable lecture hall equipped with everything you need for a great presentation.

### TOP CONFERENCE LOCATION



Inspired by Wisconsin native Frank Lloyd Wright's design, at the peak of his creative powers in 1938, the Monona Terrace Community and Convention Center is one of the country's premier conference and convention facilities.

On the shores of Lake Monona, it is an architechurally striking structure that connects the state capital, the cityscape, and the community.

Join us for golf at University Ridge Golf Course and a cruise of the Madison shoreline via private yacht with deluxe appetizers and beverages with your industry peers on **Monday**, **May 11**, the day before the conference!



### THERMOSET TOPCON

Madison, Wisconsin • May 12-13, 2020 Presented by SPE Thermoset Division

For more info and to register go to: https://spethermosets.org/topcon

> Contact teri@intuitgroup.com 248.701.8003 for info on Sponsorship and Exhibit Opportunities

